






















NR. CRT./No.	VEDERE VIEW	DIMENS. GOL HOLE DIMENSIONS (cm)		NR. BUCATI PE NIVEL NUMBER OF PIECES PER LEVEL		SUPRAFATA de DECONTARE AREA for SETTLEMENT (mp)		POZITIA IN PLAN POSITION IN PLAN	OBS. NOTES
		DM. EXEC. BUILT UP DIMENSIONS (mm)	P Ground Floor	E 1st floor	PE BUCATA per PIECE	TOTAL	DM. EXEC. BUILT UP DIMENSIONS (mm)		
0	1								
FERESTRE EXTERIOARE PE TAMPLARIE DE LEMN STRATIFICAT, CU GEAM TERMOIZOLANT, CU OCHURI MOBILE SI FIXE, CU DESCHIDERE EXTERIOARA STRATIFIED WOOD JOINERY WINDOWS, WITH THERMO-INSULATING GLASS, MOBILE AND FIXED PANES, OUTSIDE OPENING									
1		160 165			5	2.65	13.25	①	
2		150 160			1	2.40	2.40	②	
3		80 200			8	1.60	12.80	③	geam mat hammered glass
4		80 80			1	0.64	0.64	④	geam mat hammered glass
5		95 115			1	1.10	1.10	⑤	
6		135 140			10	1.90	19.00	②1	

NR. CRT./No.	VEDERE VIEW	DIMENS. GOL HOLE DIMENSIONS (cm)		NR. BUCATI PE NIVEL NUMBER OF PIECES PER LEVEL		SUPRAFATA de DECONTARE AREA for SETTLEMENT (mp)		POZITIA IN PLAN POSITION IN PLAN	OBS. NOTES
		DM. EXEC. BUILT UP DIMENSIONS (mm)	P Ground Floor	E 1st floor	PE BUCATA per PIECE	TOTAL	DM. EXEC. BUILT UP DIMENSIONS (mm)		
0	1								
FERESTRE EXTERIOARE PE TAMPLARIE DE LEMN STRATIFICAT, CU GEAM TERMOIZOLANT, CU OCHURI MOBILE, CU DESCHIDERE EXTERIOARA STRATIFIED WOOD JOINERY WINDOWS, WITH THERMO-INSULATING GLASS, MOBILE PANES, OUTSIDE OPENING									
7		55 55			3	0.30	0.90	②2	
8		80 40			1 (Subsol)	0.32	0.32	②0	ferestra de la subsol basement window
USI EXTERIOARE DIN LEMN STRATIFICAT, CU GEAM TERMOIZOLANT, IN DOUA CANATE, CU DESCHIDERE EXTERIOARA STRATIFIED WOOD DOORS, WITH THERMO-INSULATING GLASS, IN TWO LEAF, OUTSIDE OPENING									
9		160 275			2	4.40	8.80	⑧	
10		90 280			1	2.52	2.52	⑨	usa intr-un canal +overlight one wing door with window above
11		125 270			1	3.40	3.40	⑩	

NR. CRT./No.	VEDERE VIEW	DIMENS. GOL HOLE DIMENSIONS (cm)		SENS INCHIDERE CLOSING WAY	NR. BUCATI PE NIVEL NUMBER OF PIECES PER LEVEL		TOTAL BUCATI TOTAL OF PIECES	SUPRAFATA de DECONTARE AREA for SETTLEMENT (mp)		POZITIA IN PLAN MARK/POSITION IN PLAN	OBS. NOTES
		DM. EXEC. BUILT UP DIMENSIONS (mm)	P Ground Floor		E1 1st floor	PE BUC. PER PIECE		TOTAL			
0	1										
USI INTERIOARE DIN LEMN FURNIRUITE, INTR-UN CANAT INSIDE DOORS MADE OUT OF STRATIFIED WOOD, WHITE COLOUR, SOLID, SINGLE WING											
1		90 210		DR	2		6	1.90	11.40		⑭ ⑮
2		80 210		DR	1		2	1.70	3.40		⑰
3		100 210		DR	1		1	2.10	2.10		⑰
4		70 210		DR			3	1.50	4.50		⑰
5		100 215		DR			1	2.15	2.15		⑰
6		110 230		DR			1	2.55	2.55		⑰

NR. CRT./No.	VEDERE VIEW	DIMENS. GOL HOLE DIMENSIONS (cm)		SENS INCHIDERE CLOSING WAY	NR. BUCATI PE NIVEL NUMBER OF PIECES PER LEVEL		TOTAL BUCATI TOTAL OF PIECES	SUPRAFATA de DECONTARE AREA for SETTLEMENT (mp)		POZITIA IN PLAN MARK/POSITION IN PLAN	OBS. NOTES
		DM. EXEC. BUILT UP DIMENSIONS (mm)	P Ground Floor		E1 1st floor	PE BUC. PER PIECE		TOTAL			
0	1										
USI INTERIOARE DIN LEMN FURNIRUITE, INTR-UN CANAT INSIDE DOORS MADE OUT OF STRATIFIED WOOD, WHITE COLOUR, SOLID, SINGLE WING											
7		80 190		DR			1	1.55	1.55		⑮
8		150 220		DR	1		1	3.30	3.30		⑰ usi cu inchidere automata automatic closing
9		80 100		DR	1		1	0.80	0.80		⑮ glaif -caseta transfer bancar banking transfer jamb
FERESTRE INTERIOARE FIXE PE TAMPLARIE DIN LEMN STRATIFICAT SI GEAM ANTIFRACTIE INSIDE WINDOW MADE OUT OF STRATIFIED WOOD, SECURED GLASS											
10		90 210		DR	1		1	1.90	1.90		URF

**TABLOU TAMPLARIE EXTERIOARA SI INTERIOARA
EXTERIOR AND INTERIOR JOINERY BOARD**

- NOTA :
- Inainte de comandarea tamplariei se vor verifica dimensiunile exacte pentru fiecare gol de tamplarie in parte.
 - Etansarea tamplariei pe contur se va face cu spuma poliuretana.
 - Geamul termoizolant va fi compus din doua foi 4-16-4 (float clar + LOW-E) si va avea un coeficient de transfer termic minimal de 1,3W/m2R.
 - Detalii de executie a tamplariei din aluminiu se vor intoarni de catre furnizor si vor fi parte componenta a ofertei tehnice.

- Before ordering the joinery, the exact dimensions for each joinery hole will be checked separately.
- The joinery will be sealed all along the outline using polyurethane foam.
- The thermal insulating window will be made of two sheets 4-16-4 (clear float + LOW -E) and will have a minimum heat transfer coefficient of 1,3W/m2R.
- The detailed design for the aluminum joinery will be drawn up by the supplier and will be part of the technical offer.

D					
C					
B					
A					
Index	Date	Modificare	Proiectant	Approbat Consultant	Approbat CFR
		Modification/Revision	Designer	Approved Consultant	Approved CFR



CLIENT / CLIENT
CFR
C.N.C.F. "C.F.R." - S.A.



CONSULTANT / CONSULTANT		Data Date	Semnatura Signature
Approbat Approved	Şef proiect Project manager		R. Liuzza
Approbat Approved	Coordonator Seciune 1 Section 1 Coordinator		C. Gambelli
Verificat Checked	Expert Cheie Checking Expert		Giuseppe Fioravanti

SUBCONTRACTANT / SUBCONTRACTOR		Proiectant Designer	12.2011
Approbat Approved	Responsabil Subcontractant Subcontractant Responsible	A. Stanciu - Dinulescu	
Elaborat Elaborated	Proiectant Designer	Alexandra Hegedus	

Reabilitarea liniei de cale ferata Braşov - Simeria, parte componentă a coridorului IV Pan European, pentru circulația trenurilor cu viteză maximă de 160 km/h,
Tronsoanel : Braşov - Sighişoara
Rehabilitation of the railway line Braşov - Simeria, component Part of the IV Pan-European Corridor, for the trains circulation with maximum speed of 160 km/h,
Section : Braşov - Sighişoara

Denumire desen / Drawing Title :
STATIA C.F. STUPINI - CLADIRE DE CALATORI - TABLOU TAMPLARIE EXTERIOARA SI INTERIOARA RAILWAY STATION STUPINI - TRAVELERS BUILDING - EXTERIOR AND INTERIOR JOINERY BOARD

Codificare / Codification System	Scara / Scale 1:50	LOT / LOT	Nr. / No 01 / 01
E A S 1	0 1	E	0 3
B A	C C	0 0	1
1	1	0 1	7
1			