



NOTE:

1. To be used in accordance with the design specifications.

2. The reinforcement bars shall be of high yield strength.

3. The concrete shall be of high strength.

4. The joints shall be cast in situ concrete.

5. The slab shall be supported by walls or columns.

6. The slab shall be protected against fire.

7. The slab shall be protected against corrosion.

8. The slab shall be protected against acid attack.

9. The slab shall be protected against alkali-silica reaction.

10. The slab shall be protected against chloride ingress.

TABLE OF JOINTS AND REINFORCEMENT

Joint No.	Location	Reinforcement	Concrete
1	Joint 1	4x12	C30
2	Joint 2	4x12	C30
3	Joint 3	4x12	C30
4	Joint 4	4x12	C30
5	Joint 5	4x12	C30
6	Joint 6	4x12	C30
7	Joint 7	4x12	C30
8	Joint 8	4x12	C30
9	Joint 9	4x12	C30
10	Joint 10	4x12	C30

GENERAL NOTES:

1. The slab shall be cast in situ concrete.

2. The reinforcement bars shall be of high yield strength.

3. The concrete shall be of high strength.

4. The joints shall be cast in situ concrete.

5. The slab shall be supported by walls or columns.

6. The slab shall be protected against fire.

7. The slab shall be protected against corrosion.

8. The slab shall be protected against acid attack.

9. The slab shall be protected against alkali-silica reaction.

10. The slab shall be protected against chloride ingress.

APPROVED:

DATE:

PROJECT:

CLIENT:

DESIGNER:

CONTRACTOR:

REVISIONS:

No.	Description	Date
1	Issue for tender	2023-10-27
2	Issue for construction	2023-11-01
3	Issue for final approval	2023-11-15